

Area sq.mm.	A (2)	C(3)	J (4)	Ratan's Cat No.
2.5	1.9-2.1	5.4-5.6	15-17	RAC-2.5
2.5	2.5-2.7	5.4-5.6	15-17	RAC-2.5/1
4	2.8-3.0	5.4-5.6	15-17	RAC-4
6	3.4-3.6	5.4-5.6	19-21	RAC-6
10	3.7-3.9	6.1-6.3	19-21	RAC-10
10	4.3-4.5	7.1-7.3	19-21	RAC-10
16	5.3-5.5	8.2-8.4	25-27	RAC-16
25	6.8-7.1	9.6-9.8	33-37	RAC-25
35	7.8-8.1	10.7-10.9	38-42	RAC-35
50	9.1-9.4	12.9-13.1	43-47	RAC-50
70	11.1-11.4	15.4-15.6	52-58	RAC-70
95	13.0-13.3	17.3-17.5	57-63	RAC-95
120	14.5-14.9	19.5-19.7	62-68	RAC-120
150	16.2-16.6	21.4-21.6	66-74	RAC-150
185	18.2-18.6	23.9-24.1	71-79	RAC-185
240	20.7-21.3	27.9-28.2	85-95	RAC-240
300	23.5-24.1	30.9-31.2	95-105	RAC-300
400	26.5-27.1	35.4-35.7	109-121	RAC-400
500	29.5-30.2	40.9-41.2	110-131	RAC-500
630	34.5-35.2	45.9-46.2	133-147	RAC-630
800	38.5-39.2	50.9-51.2	152-168	RAC-800
1000	43.0-43.7	56.8-57.2	200-220	RAC-1000

Dimension : As per IS 8308 1993  
All dimension are in mm.

Conductivity : above 60% IACS